

FSC® Hardwood Blocks

All timber is kiln dried.
Excellent load carrying capabilities.
Very durable for site environments.

Thickness: 15, 20, 25, 30, 35, 40, 45, 50, 60, 65, 70 & 80mm
* Foiling of the hardwood can be undertaken on request.
* Further options available to aid vapour sealing.
Completely Sustainably Managed



FSC® Product Group	Product Group Specification	Product Type & Code	Input Material Category	Output Material Category	Control System For FSC Claim	Site
Insulation Blocks	FSC 100% FSC Mix	W11 Wood for Construction W11.10 Wooden Insulation	FSC 100% FSC Mix	FSC Mix	Transfer	Unit 10-15 Creekmouth Id Estate 57 River Road, Barking Essex IG11 0DA

The Forest Stewardship Council® (FSC) is an independent organisation established to promote the responsible management of the world's forests.

The FSC seeks to improve timber management, by certifying forests that are sustainably managed.

The FSC label provides a credible link between responsible production & consumption of forest products. This will enable our clients to make purchasing decisions that benefit people and the environment for generations to come.

Due to our FSC Certification, you have peace of mind that the hardwood where required, is from an FSC Certified Forest. All FSC hardwood supports produced, will be provided with a full traceability chain.



Controlled Hardwood Blocks

All timber is kiln dried.
Excellent load carrying capabilities.
Very durable for site environments.
Individually cut to suit any thermal insulation.

Thickness: 15, 20, 25, 30, 35, 40, 45, 50, 60, 65, 70 & 80mm
* Foiling of the hardwood can be undertaken on request.
* Further options available to aid vapour sealing.
Forested from sustainable managed plantations.